



12" Minimum Pipe Cover

	Appr.	Width*	Min.**
APPROACH TYPE	Min.	Max.	Radius
Residential, Three or More	24'	30'	20'
Commercial (One Way)	20'	30'	20'
Commercial (Two Way)	24'	40'	20'

- * Does not include 2' gravel shoulder on each side of approach.
- ** Or based on applicable commercial design vehicle.

NOTES:

- 1. APPROACHES SPACING SHALL CONFORM TO SECTION 3000 OF THE ACCHD MANUAL.
- 2. INGRESS/EGRESS BY FORWARD MOTION ONLY.
- 3. CULVERT PIPE SHALL BE 12" MIN. DIAMETER. CULVERT PIPE SHALL EXTEND TO THE INTERSECTION OF THE DITCH LINE AND THE 4:1 APPROACH FORESLOPE. PIPE MATERIAL SHALL BE EITHER 0.064" THICK CORRUGATED STEEL, 0.060" CORRUGATED ALUMINUM OR CLASS V REINFORCED CONCRETE.

COMMERCIAL APPROACH AND ACCESS SERVING 3 OR MORE PROPERTIES

N.T.S.

STANDARD DRAWING No. ACCHD-106 CANYON COUNTY HIGHWAY DISTRICTS CANYON COUNTY, IDAHO